





## SPECIFICATIONS

<b>Nominal Voltage (V)</b>	12V
<b>Nominal Capacity</b>	
20hour rate ( 0.9A to 10.50V )	18Ah
10hour rate ( 1.8A to 10.50V )	18Ah
5hour rate ( 3.06A to 10.20V )	15.3Ah
1C ( 18A to 9.60V )	8.1Ah
3C ( 54A to 9.60V )	6.48Ah
<b>Weight</b>	13.82 Lbs. (6.283 kg)
<b>Internal Resistance (at 1KHz)</b>	10 mΩ
<b>Maximum Discharge Current for 30 seconds :</b>	360A
<b>Maximum Discharge Current for 5 seconds :</b>	720A
<b>Operating Temperature Range</b>	
Charge	0°C(32°F) to 40°C (104°F)
Discharge	-15°C(5°F) to 50°C (122°F)
Storage	-15°C(5°F) to 40°C (104°F)
<b>Charge Retention (shelf life) at 20°C (68°F)</b>	
1 month	92%
3 month	90%
6 month	80%
<b>Charging Methods at 25°C (77°F)</b>	
Cycle use :	Charging Voltage 14.4 to 15.0V Maximum Charging Current 5.4A
Standby use :	Float Charging Voltage 13.50 to 13.80V No current limit required
<b>Life expectancy :</b>	
Cycle Use :	100% depth of discharge 250 cycles 80% depth of discharge 350 cycles 50% depth of discharge 550 cycles
Standby Use :	3~5 years
Case Material	ABS (94-HB & 94V-0 flame retardant case)
<b>Terminal</b>	F3

## Maintenance-Free Rechargeable Sealed Lead-Acid Battery



## DIMENSIONS



Vertriebspartner:



**EMG Elektromobile GmbH & Co. KG**

Düningshof 53-57 · 33729 Bielefeld · Germany

Phone: +49 (0) 521/260 380 · Fax: +49 (0) 521/260 38 20 · E-Mail: info@emg-elektromobile.com

EMG liefert u.a. Qualitätsprodukte von:

